

# 100% TEXTURIZED POLYESTER MULTICOLOR SEWING THREAD

### **Duratex Multicolor**<sup>®</sup>

DURAK Duratex Multicolor® is a multicolor sewing thread made of 100% high tenacity texturized polyester. It is injection dyed up to four different colors to give a multi-colored effect on the thread. Duratex Multicolor gives an extra special look for different-looking clothes from light-toned shades to rainbow contrasting colors. Finishing processes that increase sewing performance provide a great-looking and reliable sewing in sewing processes that require volume and flexibility with a bulky structure, high elasticity and low tensile values.



#### **Product Properties**

- Durak Duratex Multicolor® is a highly elastic and voluminous sewing thread.
- It is used on products that require elasticity and it covers the stitches perfectly due to its voluminous structure.
- Prevents shrinkage after washing with its low shrinkage values.
- Color fastness that can withstand the most challenging washing conditions.
- Improves sewing quality due to its flawless surface and special finishing processes.
- Ideal sewing thread for denim production.
- Provides a voluminous look on overlock seam.
- Dyed by injection up to 4 colors.

# **Duratex Multicolor**<sup>®</sup>

#### Areas of Use

9	Swimwear	9	Shirt
9	Home Textile	9	Babywear
9	Sportswear	C	Broidery
9	T-shirt	9	Woven Outerwear



#### **Physical Properties**

Melts at 260°C and softens at 220 - 240°C. Shrinkage is less than 1% at 150°C.

#### **Chemical Properties**

**Mineral acids:** Resistant against most mineral acids. **Alkalis:** Unaffected by weak alkalis, moderately resistant to strong alkalis.

**Organic solvents:** Unaffected by normal solvents, soluble in some phenolic compounds.

Bleaching: Unaffected. Microorganisms (Mildew/Rot): Unaffected. Washing / Dry Cleaning: Unaffected.



#### **Presentation**

DURAK Duratex Multicolor® offers a variety of meters size and thicknesses.

#### Renk Haslığı

Washing fastness at 60°C	ISO 105 C06	Min. 4
Water fastness	ISO 105 E01	Min. 4
Friction fastness	ISO 105 X12	Min. 4
Hypochlorite fastness	ISO 105 N01	Min. 4
Dry cleaning fastness	ISO 105 D01	Min. 4
Perspiration fastness	ISO 105 E04	Min. 4
Artificial light fastness	ISO 105 B02	Min. 4

#### **Storage Conditions**

Must be stored away from heat, humidity and direct sunlight.

It is recommended to use low-melting interlining for mid and dark shade multicolor threads.





# **Duratex Multicolor**<sup>®</sup>

### Thickness and Strength Chart

Ticket No.	Nominal Tex	Strength CN	Elongation %	Needle Size (Nm)
90	33	1.250	20 - 32	80 - 100
180	17	700	20 - 32	70 - 90



### Other Duratex Sub-Brands

Duratex UV ®	100% texturized polyester sewing thread with UV resistance. Duratex UV® minimizes UV destructions such as discoloration, low abrasion resistance and loss of tenacity.
Duratex OS <sup>®</sup>	100% texturized polyester sewing thread with special finishing processes in order to provide high sewing performance in the most challenging conditions. A controlled lubrication process is applied by excluding substances such as silicone, grease, graphite, wax and paraffin during the finishing process.
Duratex CFR®	100% texturized polyester sewing thread produced by adding flame-retardant characteristics. The thread surface is coated with flame retardant chemical in accordance with the standards of chemical coating method.
Duratex Recycled <sup>®</sup>	100% texturized polyester sewing thread, produced by 100% recycled polyester. It provides all the benefits a sustainable sewing thread has to offer without compromising from its sewing performance.

