




100% VISCOSE RAYON MULTICOLOR BROIDERY THREAD

Duravis Multicolor®

DURAK Duravis Multicolor® is a high quality continuous filament viscose rayon broidery thread specially produced for broidery machines. It is injection dyed up to four different colors to give a multi-colored effect on the thread. Duravis Multicolor, gives an extra special look for different-looking clothes, from light-toned shades to rainbow contrasting colors.



Areas of Use

- Broidery
- Apparel
- Home Textile
- Underwear

Product Properties

- Extra special look from light-toned shades to rainbow contrasting colors.
- Provides extra softness and comfortable.
- Vivid and brilliant appearance.
- Dyeability by injection up to 4 colors.

Duravis Multicolor®

Storage Conditions

Must be stored away from heat, humidity and direct sunlight.

Points to consider

Embroidered products made with Viscose can be washed, boiled and have light fastness. However, in order to protect the color fastness of the embroidery, the following points should be taken into consideration during washing.

- 1- Embroidered items should be washed separately and not washed with other products.
- 2- It should not be placed in the washing machine tightly, because the movement of the embroidered items inside the tub should be easy.
- 3- Embroidery products should be shaken immediately after washing, and should not be left folded or stacked when wet and damp.
- 4- Embroidered items (that do not contain chemical mixtures) should be washed with mild detergents. Heavy chemicals and bleach can cause embroidery discoloration.
- 5- Embroideries on woolen fabrics should not be washing in the machine and should not be shaken.
- 6- Stain remover or whitening products should not be used to remove stains.
- 7- Embroideries made of Viscose, can be applied with dry cleaning.
- 8- Ironing should be done on the reverse of the embroidered surface or on another fabric. During ironing, the lowest possible temperature and a steam iron should be used instead of a moist cloth.
- 9- Due to environmental reasons applied for the protection of nature, we have to change some materials used in paint and painting periodically. Therefore, despite all our efforts, there may be some slight differences between the color chart and the product.

Thickness and Strength Chart

Ticket No.	Nominal Tex	Strength CN	Elongation %	Needle Size (Nm)
50/1*2	10	300	15 - 20	*
80/1*2	16	360	15 - 20	*
120/1*2	24	620	15 - 20	*

Color Fastness

Washing fastness at 60°C	ISO 105 C06	Min. 4
Water fastness	ISO 105 E01	Min. 4
Friction fastness	ISO 105 X12	Min. 4
Dry cleaning fastness	ISO 105 D01	Min. 4
Perspiration fastness	ISO 105 E04	Min. 4

Presentation

Durak Duravis Multicolor® offers in a variety of meters size and thicknesses.

It is recommended to use low-melting interlining for mid and dark shade multicolor threads.

